

Mōrena FR

5% openness

Mōrena FR Sunscreen


Features

The 2 x 2 basketweave construction provides great stability and excellent vision out whilst controlling light, glare and heat. Selected colours are available in matching 5% and 10% openness.

Care Instructions

Dusting with a feather duster is all that is required to keep your fabric looking good. Dirt and grime can be removed by simply wiping fabric skins with a sponge soaked in lukewarm water. If marks are still visible, add a little detergent. Then dry gently with a clean cloth.

Colour Options



Charcoal

Charcoal
Bronze

Charcoal
Denim


Concrete

Graphite

Pewter

White

White
Grey



White
Linen

White
Stone



Fire retardant
AS1530 part 2



Luxaflex[®]

Mōrena FR 5% openness Sunscreen

Technical information


Fabric Density	Semi Transparent
Composition	PVC Coated Polyester Base, 2 x 2 basketweave
Weight	569gsm
Thickness	0.79mm
Width	3000mm
Colour Fastness	6 (Bluescale) Tested to ISO 105-B02:2014
Flame Retardancy	Independently tested to AS1530 part 2. Flammability Index: 5 Range [0-20]
Weave	2 x 2 Basketweave
Organic emissions (VOC)	Does not exceed the maximum VOC (Volatile Organic Compound) criteria specified by the Green Building Council of Australia (IEQ-11). Greenguard Gold Accredited
Product Options	Roller Blinds

Fabric colour	Graphite	Pewter	Charcoal	Charcoal Denim	Charcoal Bronze
---------------	----------	--------	----------	----------------	-----------------

Optical/Light properties					
Visual Light Transmittance	8%	9%	7%	9%	8%
Openness factor (nominal)	5%	5%	5%	5%	5%
Heat/Solar properties					
Solar transmittance	9%	9%	7%	9%	8%
Solar reflectance	4%	12%	3%	5%	4%
Solar absorbance	87%	79%	90%	86%	87%
G-value / Solar heat gain coefficient					
Glazing Type - Single 3mm Clear Glass	0.75	0.70	0.75	0.74	0.75

For more information please contact New Zealand Window Shades on 0800 223 224 or <http://www.luxaflex.co.nz/contact-us>

Colour options presented with data specifications



New Zealand Window Shades Ltd.
 PO Box 64019, Botany, Auckland 2163, New Zealand
 Luxaflex® is a division of New Zealand Window Shades Ltd.
 ©Copyright 2021 New Zealand Window Shades Ltd.

April 2021



Fire retardant
 AS1530 part 2



Mōrena FR 5% openness Sunscreen

Technical information

Fabric Density	Semi Transparent
Composition	PVC Coated Polyester Base, 2 x 2 basketweave
Weight	569gsm
Thickness	0.79mm
Width	3000mm
Colour Fastness	6 (Bluescale) Tested to ISO 105-B02:2014
Flame Retardancy	Independently tested to AS1530 part 2. Flammability Index: 5 Range [0-20]
Weave	2 x 2 Basketweave
Organic emissions (VOC)	Does not exceed the maximum VOC (Volatile Organic Compound) criteria specified by the Green Building Council of Australia (IEQ-11). Greenguard Gold Accredited
Product Options	Roller Blinds

Fabric colour	White	White Linen	White Grey	White Stone	Concrete
---------------	-------	-------------	------------	-------------	----------

Optical/Light properties

	White	White Linen	White Grey	White Stone	Concrete
Visual Light Transmittance	17%	14%	11%	12%	9%
Openness factor (nominal)	5%	5%	5%	5%	5%

Heat/Solar properties


	White	White Linen	White Grey	White Stone	Concrete
Solar transmittance	21%	19%	13%	16%	12%
Solar reflectance	66%	58%	42%	56%	45%
Solar absorbance	13%	23%	45%	28%	43%

G-value / Solar heat gain coefficient

Glazing Type - Single 3mm Clear Glass	White	White Linen	White Grey	White Stone	Concrete
	0.34	0.40	0.50	0.41	0.48

For more information please contact New Zealand Window Shades on 0800 223 224 or <http://www.luxaflex.co.nz/contact-us>

Colour options presented with data specifications



White White Linen White Grey White Stone Concrete

New Zealand Window Shades Ltd.
 PO Box 64019, Botany, Auckland 2163, New Zealand
 Luxaflex® is a division of New Zealand Window Shades Ltd.
 ©Copyright 2021 New Zealand Window Shades Ltd.

April 2021



Fire retardant
 AS1530 part 2

