

5% opennessEcolibrium Sunscreen

Features

Ecolibrium is a 2x2 sunscreen manufactured using bio based plasticisers, rather than fossil fuel based plasticisers. This type of plasticiser does not detract from the sunscreen's appearance or performance, and provides a sustainable green alternative to traditional sunscreens, without the PVC smell.

Care Instructions

Fabric should be regularly dusted / vacuumed as appropriate. May be wiped with warm water and mild detergent.

Colour Options









Ecolibrium 5% openness Sunscreen

Technical information

Fabric Density	Semi Transparent
Composition	25% Polyester, 75% Vinyl on Polyester (over 50% of compound components are derived from crop based feed stocks and minerals. Over 2/3 of total compound is derived from non fossil fuel based feed stocks).
Weight	488gsm
Thickness	0.61mm
Width	3200mm
Flame Retardancy	Independently tested to AS1530 part 2. Flammability Index: 4 Range [0-20]
Weave	Basketweave
Organic emissions (VOC)	Does not exceed the maximum VOC (Volatile Organic Compound) criteria specified by the Green Building Council of Australia (IEQ-11).
Product Options	Roller Blinds

Fabric colour	Charcoal	White	White Linen	White Grey	White Stone
Optical/Light properties					
Visual Light Transmittance	7%	11%	13%	11%	12%
Openness factor (nominal)	5%	5%	5%	5%	5%
Heat/Solar properties					
Solar transmittance	5%	12%	13%	10%	12%
Solar reflectance	3%	74%	62%	49%	61%
Solar absorbance	92%	14%	25%	41%	27%
G-value / Solar heat gain coefficient					
Glazing Type - Single 3mm Clear Glass	0.74	0.26	0.35	0.44	0.36

For more information please contact New Zealand Window Shades on 0800 223 224 or http://www.luxaflex.co.nz/contact-us

Colour options presented with data specifications



New Zealand Window Shades Ltd.
PO Box 12 785, Penrose , Auckland 1642, New Zealand
Luxaflex® is a division of New Zealand Window Shades Ltd.

©Copyright 2019 New Zealand Window Shades Ltd.







Ecolibrium 5% openness Sunscreen

Technical information

Fabric Density	Semi Transparent
Composition	25% Polyester, 75% Vinyl on Polyester (over 50% of compound components are derived from crop based feed stocks and minerals. Over 2/3 of total compound is derived from non fossil fuel based feed stocks).
Weight	488gsm
Thickness	0.61mm
Width	3200mm
Flame Retardancy	Independently tested to AS1530 part 2. Flammability Index: 4 Range [0-20]
Weave	Basketweave
Organic emissions (VOC)	Does not exceed the maximum VOC (Volatile Organic Compound) criteria specified by the Green Building Council of Australia (IEQ-11).
Product Options	Roller Blinds

Fabric colour	Linen	Sandstone	Charcoal Gold	Charcoal Grey	Charcoal Bronze
Optical/Light properties					
Visual Light Transmittance	11%	9%	9%	10%	9%
Openness factor (nominal)	5%	5%	5%	5%	5%
Heat/Solar properties					
Solar transmittance	10%	8%	6%	7%	7%
Solar reflectance	47%	40%	18%	10%	5%
Solar absorbance	43%	52%	76%	83%	88%
G-value / Solar heat gain coefficient					
Glazing Type - Single 3mm Clear Glass	0.44	0.36	0.61	0.67	0.7

For more information please contact New Zealand Window Shades on 0800 223 224 or http://www.luxaflex.co.nz/contact-us

Colour options presented with data specifications



New Zealand Window Shades Ltd.
PO Box 12 785, Penrose , Auckland 1642, New Zealand
Luxaflex® is a division of New Zealand Window Shades Ltd.

©Copyright 2019 New Zealand Window Shades Ltd.





